

Combination & Combination Plus Storm Windows

Our **Combination** storm and screen window has a fixed charcoal fiberglass screen adhered to the outside of the storm window. A white or brown aluminum-framed clear annealed glass storm insert is provided for each section of the window. The framing includes vinyl glazing strip and pile weather seal. We secure each panel in place using eight clear flush panel clips (two on each edge). If the window is small enough that a center bar is not needed, additional panel clips may be used.

The **Combination Plus** storm and screen window includes two inserts for both the upper and lower sections of the window: a brown or white aluminum-framed clear annealed glass storm insert as well as an aluminum-framed charcoal fiberglass screen insert. The framing includes vinyl glazing strip and pile weather seal. We secure each panel in place using eight clear flush panel clips (two on each edge). If the window is small enough that a center bar is not needed, additional panel clips may be used.

Adams Standard Profiles:		Thickness:	1-1/8"
Top Rail Width:	2-1/8"	Bottom Rail Width:	3-1/2"
Stile Width:	2-1/8"	Center Bar Width:	2-1/8"



Combination &
Combination Plus
VIEW FROM INTERIOR



Combination
VIEW FROM EXTERIOR



Combination Plus
VIEW FROM EXTERIOR

Options:	
<ul style="list-style-type: none"> ▪ Factory priming ▪ Custom glass (Restoration, low-E, etc.) ▪ Custom shapes (half round top, arched top, rounded corners, etc.) 	<ul style="list-style-type: none"> ▪ Preservative treatment ▪ Wood Specie (Mahogany, Douglas Fir, etc.)